

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 801 938 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
22.10.1997 Bulletin 1997/43(51) Int. Cl.<sup>5</sup>: A61F 7/12

(21) Application number: 97106282.3

(22) Date of filing: 16.04.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FR GB IT LI NL SE

(30) Priority: 16.04.1996 US 632630

(71) Applicant: ARGOMED Ltd.  
46766 Herzlia Pituach (IL)(72) Inventors:  
• Eshel, Uzi  
Herzlia (IL)

- Crabtree, Graham J.  
Herzlia (IL)
- Lazarovitz, Jacob  
Hod Hasharon (IL)

(74) Representative: von Samson-  
Himmelsjerna, Friedrich R., Dipl.-Phys. et al  
SAMSON & PARTNER  
Widenmayerstrasse 5  
80538 München (DE)

## (54) Thermal treatment apparatus

(57) A temperature-setting device for providing a predetermined temperature to a quantity of fluid circulating therethrough, a thermal treatment apparatus including such device for selectively treating a targeted tissue adjacent a subject's body cavity, and techniques using such thermal treatment apparatus are provided. The temperature-setting device comprises: an electrically conducting tubular element, a housing element for receiving the tubular element; and a transformer electrically connectable to the housing element. The tubular element functions as a resistor and heats the fluid circulating therethrough. Alternatively, the housing element comprises a thermal conducting member disposed within a bath of a cooling substance, the thermal conducting member having a recess for receiving the tubular element. The tubular element may alternately be placed in a housing element functioning as a heater and a housing element functioning as a cooler, thereby alternately heating or cooling the fluid circulating therethrough. The thermal treatment apparatus comprises: a temperature-setting device according to the present invention; a catheter insertable into a subject's body cavity, the catheter including a thermal treating section for thermally treating a targeted tissue; a pump; thermal sensor assemblies; and an air trapping element.




FIG. 1

EP 0 801 938 A2

## Description

## SUMMARY OF THE INVENTION

## FIELD AND BACKGROUND OF THE INVENTION

The present invention relates to a temperature-setting device which can be used to provide a desired temperature to a minimal quantity of fluid circulating in a closed system.

Also the present invention relates to a thermal treatment apparatus including such temperature-setting device for selectively treating a targeted tissue by applying fluid-induced thermal therapy, as disclosed in U.S. Pat. No. 5,257,977 (and described in U.S. Pat. No. 5,549,559 published after the priority date of the present application).

Fluid induced thermal therapy is based on localized heating of a targeted tissue to a predetermined temperature by means of circulating fluid, while keeping the temperature of adjacent healthy tissues unchanged. Relative to therapy methods which use laser, microwave, radiofrequency and ultrasound to produce heat within a tissue, the fluid-induced thermotherapy allows better control of the temperature and the limits of the treated site.

Alternatively, a thermal treatment apparatus according to the present invention may be used for selectively preserving a portion of a tissue treated by cryosurgery, by selectively heating that portion of the tissue.

Various attempts have been made to provide devices for heating an amount of fluid circulating in a closed systems such as fluid-induced thermal therapy systems. Prior art includes heating bath circulators and a heater based on a container serving as a water reservoir. (An example is disclosed in U.S. Pat. No. 5,549,559.)

However, such configurations consume a considerable amount of energy, since a large quantity of fluid has to be heated (or cooled). Moreover, a considerable damage may be caused in the event of system's failure, by the leakage of a large quantity of fluid into the body cavity.

There is thus a widely recognized need for, and it would be highly advantageous to have, a device which can provide a desired temperature to a minimal quantity of fluid which circulates in a closed system such as fluid-induced thermal therapy system.

It would be further advantageous to have such device which allows to alternately heat and cool a component of such closed system by alternately placing such component in embodiments of the device functioning as heaters and coolers.

It would be further advantageous to have a thermal treatment apparatus for selectively treating a targeted tissue by fluid-induced thermal therapy, which uses a minimal quantity of circulating fluid and therefore consumes minimal energy for heating (or cooling) the fluid, and minimizes the possible damage in the event of fluid leakage.

According to the present invention there is provided a temperature-setting device for providing a predetermined temperature to a minimal quantity of fluid circulating therethrough, comprising: (a) a tubular element having a relatively low electrical conductivity for receiving a quantity of circulating fluid; (b) a housing element for receiving and anchoring said tubular element therein, and for electrically connecting the tubular element to an electrical circuit; and (c) a transformer element electrically connectable to the electrical circuit.

According to further features in preferred embodiments of the invention described below, the tubular element has two ends connectable to electrically and thermally insulating tubular elements.

Further, the housing element includes fastening elements, comprising: a connector member having a relatively good electrical conductivity, connectable to an electrical circuit; and fastening member for anchoring the tubular member between the fastening member and the connector member.

According to still further features in the described preferred embodiments, the temperature-setting device may include a sensor for sensing the temperature of the tubular element.

The sensor and the transformer element may be electrically connected to a controller. In such configuration, the controller may control the duty cycle of the transformer according to the temperature sensed by the sensor. Alternatively, the controller may interrupt the operation of the transformer and the electrical circuit upon over-heating of the tubular element.

The tubular element and the insulating tubular elements may be disposable.

According to another embodiment, the housing element comprises a thermal conducting member disposed within a bath of a cooling substance, the thermal conducting member featuring a recess for receiving the tubular element therein. The recess preferably defines a lowered area relative to the surface of the cooling substance, for trapping cold air. The recess may be used for receiving a small quantity of fluid for improving the thermal coupling between the thermal conducting member and the tubular element.

According to further features of this embodiment, the thermal conducting member features extensions for increasing the area of contact between the thermal conducting member and the cooling substance.

The tubular element may alternately be placed in embodiments functioning as heaters and embodiments functioning as coolers, thereby alternately heating and cooling the fluid circulating therethrough.

According to yet another embodiment, the housing element is in the form of two thermal conducting plates, each of which controllably connectable to a heating and/or cooling source such as a pettier heat pump element.

Each of the thermal conducting plates may feature

a recess, the recesses defining a tunnel for receiving the tubular element therein, preferably under pressure.

The thermal conducting plates may alternately heat and cool the tubular element, thereby alternately heating and cooling the fluid circulating therethrough.

Also according to the present invention there is provided a thermal treatment apparatus which uses fluid-induced thermal therapy for selectively treating a targeted tissue adjacent to a subject's body cavity. The thermal treatment apparatus comprises a closed system of circulating fluid and a controller for controlling the closed system, the closed system including: (a) a temperature-setting device according to the present invention; (b) a catheter insertable into a body cavity, the catheter connectable to the temperature-setting device and including a thermal treating section for thermally treating a targeted tissue adjacent the body cavity by circulating fluid of a predetermined temperature through the thermal treating section; (c) a pump for pumping the fluid of predetermined temperature through the closed system; and (d) thermal sensor assembly for sensing the temperature of fluid circulating into the catheter.

According to further features in preferred embodiments of the invention described below, the thermal treatment apparatus may further include a second thermal sensor assembly for sensing the temperature of fluid circulating out of the catheter.

According to still further features in preferred embodiments of the invention described below, the thermal treatment apparatus may include an air trapping element, for trapping air circulating in the system.

The present invention successfully addresses the shortcomings of the presently known configurations by providing a temperature-setting device for providing a predetermined temperature to a minimal quantity of fluid circulating in a closed system.

Further, the present invention provides a thermal treatment apparatus for selectively treating a targeted tissue by fluid-induced thermal therapy, comprising a closed system of circulating fluid which uses a minimal quantity of fluid and therefore consumes minimal energy for heating (or cooling) the fluid, and minimizes the possible damage in the event of fluid leakage; and which further uses temperature control which is completely external to the patient's body.

The present invention discloses a novel temperature-setting device which allows to alternately heat and cool a component of such closed system, the component being in the form of a tubular element having relatively good thermal conductivity, by alternately placing the component in embodiments of the device functioning as heaters and embodiments functioning as coolers.

A technique for selectively thermally treating a targeted tissue adjacent a subject's body cavity comprises the steps of: (a) inserting into a subject's body cavity a catheter, including a thermal treating section for thermally treating said targeted tissue adjacent to the body cavity by circulating fluid of a predetermined temperature through said thermal treating section, the catheter

being disposable; (b) heating fluid circulating in a closed system including the catheter, and further including: a pump for pumping fluid through the closed system; thermal sensor assemblies for sensing the temperature of fluid circulating into and out of the catheter; and a temperature-setting device for heating the fluid circulating therethrough, the temperature-setting device including: (i) a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to electrically and thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; (ii) a housing element for receiving the tubular element, the housing element including fastening elements, including: a connector member having relatively good electrical conductivity, the connector member connectable to an electrical circuit; and a fastening member for anchoring the tubular element between the fastening member and the connector member; (iii) a transformer element connectable to the electrical circuit, the transformer element electrically connected to the controller.

The catheter may include a proximal end formed with an inflatable thermal treating section to be located within the body cavity, and a distal end to be located externally of the body cavity; the catheter being formed with first and second passageways extending from the distal end to the inflatable thermal treating section for circulating fluid of a predetermined temperature through the inflatable thermal treating section.

The catheter may include a proximal end formed with an inflatable anchoring section for anchoring the catheter in the body cavity, a distal end to be located externally of the body cavity, and an inflatable thermal treating section adjacent the proximal end to be located near the targeted tissue; the catheter being formed with first and second passageways extending from the distal end to the inflatable thermal treating section for circulating fluid of a predetermined temperature through the inflatable thermal treating section, and a third passageway extending from the distal end to the inflatable anchoring section for introducing unheated fluid into the inflatable anchoring section.

The catheter may further include thermal insulation surrounding the first and second passageways from close to the distal end to close to the inflatable thermal section, the thermal insulation including a plurality of separate compartments containing a non-heated fluid, the compartments extending axially along the catheter, thereby the inflatable thermal treating section and the targeted tissue in its proximity may be heated to a desired temperature without correspondingly heating non-targeted tissues.

The tubular element of the temperature-setting device, the insulating tubular elements and other tubular elements constituting the closed system may be disposable.

The pump may include: (a) a housing formed with a substantially cylindrical cavity having an inner surface,

the housing provided with a lid, the lid having a depending skirt removably engageable within the cylindrical cavity so as to form an inset lining around a part of the inner surface; (b) a rotor rotatably mounted within the cylindrical cavity, the rotor carrying rollers; and (c) a peristaltic tube, the peristaltic tube being disposable, such that, when the depending skirt is not engaged in the cylindrical cavity, the peristaltic tube may be easily inserted between the rollers and the inner surface and, when the depending skirt is engaged in the cylindrical cavity, the peristaltic tube is engaged between the rollers and the inset lining such that rotation of the rotor pumps fluid through the peristaltic tube.

The thermal sensor assembly may include: a thermal sensor; a disposable metal tube connectable to the end of a passageway of the catheter to receive the fluid flowing therethrough; a metal thermal coupling member formed with a recess on one face for receiving the thermal sensor therein, a recess on the opposite face complementary to the shape of the metal tube for receiving the metal tube therein, and a relatively thin web between the two recesses; and a cover pressing the metal tube to the thermal coupling member.

The apparatus used in the technique for selectively thermally treating a targeted tissue may further include an air trapping element for trapping air circulating in the system, the air trapping element comprising a hung container controllably connectable to the closed system, the air trapping element being disposable.

A further technique for selectively thermally treating a targeted tissue adjacent to a subject's body cavity comprises the steps of: (a) inserting into a subject's body cavity a catheter, including a thermal treating section for thermally treating the targeted tissue adjacent the body cavity by circulating fluid of a predetermined temperature through the thermal treating section, the catheter being disposable; (b) alternately heating and cooling fluid circulating in a closed system including the catheter, and further including: a pump for pumping fluid through the closed system; thermal sensor assemblies for sensing the temperature of fluid circulating into and out of the catheter; and a temperature-setting device for alternately heating and cooling the fluid circulating therethrough, the temperature-setting device comprising: a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to electrically and thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; a heating housing element for receiving the tubular element, the housing element detachably connectable to a heating source; and a cooling housing element for receiving the tubular element, the housing element detachably connectable to a cooling source, the tubular element transferable between the heating housing element and the cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

The temperature-setting device may comprise: (a)

a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to electrically and thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; (b) a heating housing element for receiving the tubular element, the housing element including fastening elements, including: (i) a connector member having relatively good electrical conductivity, the connector member connectable to an electrical circuit; (ii) a fastening member for anchoring the tubular element between the fastening member and the connector member; (c) a transformer element connectable to the electrical circuit, the transformer element electrically connected to the controller; and (d) a cooling housing element comprising a thermal conducting member disposed within a bath of a cooling substance, the thermal conducting member having a recess for receiving the tubular element, the recess defining a relatively lowered area for trapping cold air, the thermal conducting member featuring extensions for increasing the contact area between the thermal conducting member and the cooling substance; the tubular element transferable between the heating housing element and the cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

A technique for selectively thermally treating a targeted tissue adjacent a subject's body cavity may comprise the steps of: (a) inserting into a subject's body cavity a catheter, including a thermal treating section for thermally treating the targeted tissue adjacent the body cavity by circulating fluid of a predetermined temperature through the thermal treating section, the catheter being disposable; (b) alternately heating and cooling fluid circulating in a closed system including the catheter, and further including: a pump for pumping fluid through the closed system; thermal sensor assemblies for sensing the temperature of fluid circulating into and out of the catheter; and a temperature-setting device for alternately heating and cooling the fluid circulating therethrough, the temperature-setting device comprising: (i) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; (ii) a housing element for alternately heating and cooling the tubular element, the housing element comprising two thermal conducting plates, each having a recess, the recesses defining a tunnel for receiving the tubular element under pressure; (iii) a heating source detachably connectable to the housing element; and (iv) a cooling source detachably connectable to the housing element; the housing element alternately heating and cooling the tubular element, thereby alternately heating and cooling the fluid circulating therethrough.

The temperature-setting device may comprise: (a) a tubular element having relatively good thermal con-

ductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; (b) a housing element for alternately heating and cooling said tubular element, the housing element comprising two thermal conducting plates, each having a recess, the recesses defining a tunnel for receiving the tubular element under pressure; and (c) peltier heat pump elements detachably connectable to the thermal conducting plates, the peltier heat pump elements alternately heating and cooling the thermal conducting plates, thereby alternately heating and cooling the fluid circulating through the tubular element.

A technique for selectively thermally treating a targeted tissue adjacent a subject's body cavity may comprise the steps of: (a) inserting into a subject's body cavity a catheter, including a thermal treating section for thermally treating the targeted tissue adjacent the body cavity by circulating fluid of a predetermined temperature through the thermal treating section, the catheter being disposable; (b) heating fluid circulating in a closed system including the catheter, and further including: a pump for pumping fluid through the closed system; thermal sensor assemblies for sensing the temperature of fluid circulating into and out of the catheter; and a temperature-setting device for heating the fluid circulating therethrough, the temperature-setting device comprising: (i) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, the tubular element having two ends connectable to thermally insulating tubular elements, the tubular element and the insulating tubular elements being disposable; (ii) a housing element for heating the tubular element, the housing element comprising two thermal conducting plates, each having a recess, the recesses defining a tunnel for receiving the tubular element under pressure; and (iii) a heating source detachably connectable to the housing element.

The catheter may include a proximal end formed with an inflatable thermal treating section to be located within the body cavity, and a distal end to be located externally of the body cavity; the catheter being formed with first and second passageways extending from the distal end to the inflatable thermal treating section for circulating fluid of a predetermined temperature through the inflatable thermal treating section.

The catheter may include a proximal end formed with an inflatable anchoring section for anchoring the catheter in the body cavity, distal end to be located externally of the body cavity, and an inflatable thermal treating section adjacent the proximal end to be located near the targeted tissue; the catheter being formed with first and second passageways extending from the distal end to the inflatable thermal treating section for circulating fluid of a predetermined temperature through the said inflatable thermal treating section, and a third passageway extending from the distal end to the inflatable anchoring section for introducing unheated fluid into the

inflatable anchoring section.

The catheter may further include thermal insulation surrounding the first and second passageways from close to the distal end to close to the inflatable thermal section, the thermal insulation including a plurality of separate compartments containing a non-heated fluid, the compartments extending axially along the catheter, thereby the inflatable thermal treating section and the targeted tissue in its proximity may be heated to a desired temperature without correspondingly heating non-targeted tissues.

The invention may be summarized as follows: A temperature-setting device for providing a predetermined temperature to a quantity of fluid circulating therethrough, a thermal treatment apparatus including such device for selectively treating a targeted tissue adjacent a subject's body cavity, and techniques using such thermal treatment apparatus are provided. The temperature-setting device may comprise: an electrically conducting tubular element, a housing element for receiving the tubular element; and a transformer electrically connectable to the housing element. The tubular element functions as a resistor and heats the fluid circulating therethrough. Alternatively, the housing element comprises a thermal conducting member disposed within a bath of a cooling substance, the thermal conducting member having a recess for receiving the tubular element. The tubular element may alternately be placed in a housing element functioning as a heater and a housing element functioning as a cooler, thereby alternately heating or cooling the fluid circulating therethrough. The thermal treatment apparatus may comprise: a temperature-setting device according to the present invention; a catheter insertable into a subject's body cavity, the catheter including a thermal treating section for thermally treating a targeted tissue; a pump; thermal sensor assemblies; and an air trapping element.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

FIG. 1 is a schematic diagram illustrating an embodiment of a temperature-setting device and other main components of a thermal treatment apparatus according to the present invention;

FIG. 2a is a transverse sectional view of another embodiment of a temperature-setting device according to the present invention, along lines A-A in FIG. 2b.

FIG. 2b is a longitudinal sectional view of the embodiment shown in FIG. 2a, along line B-B.

FIG. 3a is a transverse sectional view of yet another embodiment of a temperature-setting device according to the present invention, along lines A-A in FIG. 3b.

FIG. 3b is a top view of the embodiment shown in

FIG. 3a.

FIG. 4a is a side view, partially in longitudinal section, of a catheter according to the present invention;

FIG. 4b is a side view, partially in longitudinal section, of the catheter illustrated in FIG. 4a rotated 90°.

FIG. 5a, 5b and 5c are transverse sectional views of the catheter shown in FIG. 4b, along lines A-A, B-B and C-C.

FIG. 6 is a side view, partially in longitudinal section, of another embodiment of a catheter according to the present invention, in which the anchoring section is an integral part of the thermal treating section;

FIG. 7a, 7b and 7c are transverse sectional views of the catheter shown in FIG. 6, along lines A-A, B-B and C-C.

FIG. 8a is a longitudinal sectional view of a peristaltic pump according to the present invention, along line A-A in FIG. 8b;

FIG. 8b is a transverse sectional view of the peristaltic pump shown in FIG. 8a, along line B-B;

FIG. 8c is a fragmentary detail view along line C-C in FIG. 8b;

FIG. 9a is a top view of an embodiment of a thermal sensor assembly according to the present invention.

FIG. 9b is a fragmentary detail view of the thermal sensor assembly shown in FIG. 9a, along line B-B.

FIG. 9c is a transverse sectional view of the thermal sensor assembly shown in FIG. 9a, along line C-C.

FIG. 10a is a transverse sectional view of another embodiment of a thermal sensor assembly, along line A-A in FIG. 10b.

FIG. 10b is a longitudinal sectional view of the thermal sensor assembly shown in FIG. 10a, along line B-B.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is of a temperature-setting device for providing a desired temperature to a minimal quantity of fluid circulating in a closed system.

Also the present invention is of a thermal treatment apparatus including such device, for selectively treating a targeted tissue by fluid-induced thermal therapy using a minimal quantity of circulating fluid and consuming minimal energy for heating (or cooling) the fluid.

The principles and operation of a temperature-setting device according to the present invention and of a thermal treatment apparatus including such device may be better understood with reference to the drawings and the accompanying description.

FIG. 1 illustrates a thermal treatment apparatus which uses fluid-induced thermal therapy for selectively treating a targeted tissue adjacent a subject's body cavity. The thermal treatment apparatus comprises a

closed system, including: a temperature-setting device 4 for providing a desired temperature to a minimal quantity of fluid circulating through the system; a catheter 2 insertable into the subject's body cavity and connectable to temperature-setting device 4; a pump 6 for pumping the fluid through the system, the pump connectable to temperature-setting device 4; and preferably two thermal sensor assemblies 8 and 10 for measuring the temperature of fluid circulating into and out of catheter 2, respectively. Preferably, the closed system further includes an air trapping element 7 for trapping air circulating in the closed system.

The thermal treatment apparatus further includes a controller 12 for controlling the operation of temperature-setting device 4 and pump 6, preferably according to the temperature sensed by thermal sensor assemblies 8 and 10.

As shown in FIG. 1, a temperature-setting device according to the present invention includes a resistive tubular element 3 having relatively low electrical conductivity and good thermal conductivity. Tubular element 3 may be made, for example, of stainless steel. Tubular element 3 is preferably disposable.

Preferably, temperature-setting device 4 further includes a housing element (not shown) having a recess for receiving tubular element 3. The housing element preferably includes two fastening elements 5 for mechanically anchoring tubular element 3 in the housing element, and electrically connecting the ends of tubular element 3 to a transformer 11. Each of fastening elements 5 comprises two components 5a and 5b. Component 5a preferably includes a fastening member such as a screwing element for anchoring tubular element 3 between component 5a and component 5b. Component 5b has relatively good electrical conductivity for allowing electrical connection between tubular element 3 and transformer 11.

Since tubular element 3 has relatively low electrical conductivity, it functions as a resistor and converts electrical energy to heat, thereby heating the fluid circulating therethrough. This configuration allows to circulate a minimal quantity of heated fluid through the system. Preferably, the quantity of circulating fluid is about 20-50 ml.

The voltage produced by transformer 11 is preferably very low, about 1-5 volts, in order to provide the necessary safety while using the device.

Preferably, temperature-setting device 4 further includes a temperature sensor 7 located at the housing element, for sensing the temperature of tubular element 3. The connection between sensor 7 and tubular element 3 is preferably established readily upon mounting of element 3 in the housing element, under pressure.

Sensor 7 is electrically connected to controller 12. Controller 12 may control the duty cycle of transformer 11 according to the temperature sensed by sensor 7, where the duty cycle refers to the time intervals during which transformer 11 provides electrical current or voltage to the system. Additionally, sensor 7 may function

as a safety switch, so that when fluid circulation in the system is interrupted, sensor 7 heats up and consequently controller 12 preferably interrupts the operation of the overall system.

Alternatively, controller 12 may control the duty cycle of transformer 11 according to the temperature sensed by thermal sensor assemblies 8 and 10.

Referring now to FIGs. 2a and 2b, according to another embodiment of temperature-setting device 4, the housing element comprises a thermal conducting member 14 disposed within a bath 13 of a cooling substance 15, such as ice. Thermal conducting member 14 preferably features a recess 14a for receiving tubular element 3 therein. Recess 14a preferably defines a lowered area relative to the surface 15a of cooling substance 15, for trapping cold air. This configuration creates a local well of cold air defined by recess 14a, for efficiently cooling tubular element 3. Further, recess 14a may be used for receiving a quantity of fluid for improving the thermal coupling between thermal conducting member 14b and tubular element 3. Preferably, thermal conducting member 14 further features extensions 14b for increasing the area of contact between thermal conducting member 14 and cooling substance 15. Preferably, the housing element is stored under freezing conditions while not in use.

Temperature-setting device 4 may be used to alternately heat and cool a minimal quantity of fluid circulating through the system, by alternately placing tubular element 3 in embodiments of the device functioning as heaters (e.g. the configuration shown in FIG. 1) and embodiments functioning as coolers (e.g. the configuration shown in FIGs. 2a and 2b). While using the configuration of FIGs. 2a and 2b, transformer 11 is not used.

Referring now to FIGs. 3a and 3b, according to yet another embodiment of temperature-setting device 4, the housing element comprises two plates 16a and 16b, made of a material having relatively good thermal conductivity such as aluminum. Plates 16a and 16b are controllably connectable to heating and/or cooling sources 17 and 18, respectively. Heating and/or cooling sources 17 and 18 may be, for example, pellicer heat pump elements. As shown, each of plates 16a and 16b may feature a recess, the recesses defining a tunnel for receiving tubular element 3 therein, preferably under pressure. This configuration allows better thermal coupling between thermal conducting plates 16a and 16b and tubular element 3.

While using this configuration, tubular element 3 is placed within the recess of plate 16b. Plate 16a is then placed on top of plate 16b, covering tubular element 3 so that tubular element 3 is preferably pressed within the tunnel defined by the recesses of plates 16a and 16b.

This configuration may be used as a heater and/or cooler, according to the function (heating or cooling) performed by sources 17 and 18. While using this configuration, transformer 11 is not used.

Referring now to FIGs. 4-7, thermal treatment

apparatus according to the present invention further includes a catheter 2 connectable to temperature-setting device 4 and insertable into a subject's body cavity such as urinary bladder, prostatic urethra, uterus and esophagus, for selectively treating a targeted tissue within or near such cavity.

For example, selective treatment of a subject's prostate gland may be accomplished by inserting catheter 2 into the subject's urinary tract and anchoring catheter 2 within the subject's bladder. As shown in FIGs. 4a, 4b and 5a, 5b and 5c, catheter 2 preferably includes a long slender tube 20 formed with an inflatable anchoring section 21 at the proximal end for anchoring the catheter in the subject's body cavity, and thereby locating an inflatable cylindrical thermal treating section 22 near the targeted tissue to be treated. The length of thermal treating section 22 may preferably be adapted according to the distance between the bladder neck and the verumontanum of the particular patient. The distal end of catheter 23 is to be located externally of the subject's body so as to be readily accessible for inflating anchoring section 21 and thermal treating section 22.

A limited quantity of fluid having a predetermined temperature is circulated through inflatable thermal treating section 22 via two passageways 24a and 24b having an inlet 25 and an outlet 26 at distal end 23 of the catheter. As shown in FIG. 1, a valve member 2a is connected to outlet 26 of the catheter for introducing fluid into the closed system.

Inflatable anchoring section 21 of the catheter is preferably inflated by an amount of unheated fluid introduced via inlet 27 at distal end 23 of the catheter. Inlet 27 preferably communicates with anchoring section 21 via an unheated-fluid passageway 28 and an opening 29.

The portion of the catheter from distal end 23 to inflatable thermal treating section 22 is preferably thermally insulated from the subject's untargeted tissues by means of insulating chambers 30 enclosing passageways 24a and 24b. One of insulating chambers 30 preferably communicates with unheated-fluid passageway 28 through which unheated air is applied to inflate anchoring section 21.

The catheter also includes an extension 31 at the proximal end, which extension is received within the subject's body cavity. Extension 31 is formed with an opening 32 for draining body fluids via draining passageway 33 passing through the length of the catheter and terminating in an outlet 34 attachable to a drain. Alternatively, passageway 33 may be used for introducing a drug into the subject's body cavity. Further, passageway 33 may be used for introducing a stiffening element for facilitating the insertion of the catheter to the subject's body cavity.

Catheter 2 and valve member 2a are preferably disposable.

According to another configuration (not shown), catheter 2 includes only one chamber 30 for communicating with inlet 27 and passageway 28 through which

unheated air is applied to inflate anchoring section 21, so that passageways 24a and 24b along slender tube 20 are not insulated.

Yet another configuration of catheter 2 is shown in FIGs. 6 and 7a, 7b and 7c. In this configuration, anchoring section 21 is made as an integral part of thermal treating section 22, and passageway 28 is missing. Further, thermal treating section 22 may feature any geometrical shape, according to the specific geometry of the subject's body cavity. Such configuration may be used, for example, for endometrial ablation, where the geometry of thermal treating section 22 is adapted to fit the specific geometry of a subject's uterus, and insulating chambers 30 enable the use of a heating source for heating the fluid, which is completely external to the subject's body.

According to additional configuration (not shown), anchoring section 21 is made as an integral part of thermal treating section 22, and all of chambers 30, inlet 27 and passageway 28 are missing, so that passageways 24a and 24b along slender tube 20 are not insulated. Inflatable thermal treating section 22 may feature any geometrical shape, according to the specific geometry of the subject's body cavity. Such configuration may be used, for example, for selectively heating a portion of a tissue treated by cryosurgery, thereby preserving that portion.

Referring now to FIGs. 8a, 8b and 8c, thermal treatment apparatus according to the present invention further includes a pump 6 connectable to catheter 2 and temperature-setting device 4. Pump 6 is preferably a peristaltic pump, and includes a housing 60 formed with a cylindrical cavity 61. Disposed within cylindrical cavity 61 is a rotor 62 connected by a drive shaft 63 to a gear motor (not shown) and including a pair of spaced discs 64a, 64b rotatably mounting between them a plurality (3) of rollers 65 within cavity 61. Also located within cylindrical cavity 61 is a peristaltic tube 66 which is engageable by roller 65 for pumping the fluid through the tube during the rotation of rotor 62. Assuming rotor 62 is rotated counter-clockwise in FIG. 8b, the fluid will be pumped through peristaltic tube 66 from an inlet nipple 67 to an outlet nipple 68.

As shown in FIG. 8a, housing 60 further includes a lid 70 with a large central opening 71 for accommodating disc 64a of rotor 62. Lid 70 is formed with a depending skirt 72 which extends into cylindrical cavity 61 such that peristaltic tube 66 is located between the inner surface of skirt 72 and rollers 65. Skirt 72 extends only for a part of the circumference of the lid, e.g., from 160° to 200°, to accommodate the inlet and outlet ends of peristaltic tube 66. As shown in FIG. 8b, skirt 72 extends slightly more than 180°; also, its leading edge 73 and its trailing edge 74 are tapered to provide a gradual application of pressure to the peristaltic tube by roller 65, and a gradual release of the pressure. Peristaltic tube 66 is preferably disposable.

Preferably, housing 60 features two or more pins 75, and lid 70 features two or more depressions 75a

respectively for receiving pins 75 therein. Such configuration prevents the rotation of lid 70 during rotation of rotor 62.

The illustrated construction, including depending skirt 72, facilitates the assembly of the peristaltic pump with peristaltic tube 66 between skirt 72 and rollers 65. Thus, with the lid removed peristaltic tube 66 may be conveniently applied around rollers 65. Lid 70 may then be applied with its skirt 72 received between peristaltic tube 66 and the inner surface of cylindrical cavity 61 formed in housing 60, so as to squeeze the tube between skirt 72 and rollers 65. Accordingly, the lower edge of skirt 72 is tapered, as shown at 76 in FIG. 8a, for facilitating the application of the skirt.

The foregoing construction not only facilitates the assembly of the peristaltic pump, but also covers rollers 65 to minimize exposure to a person's fingers or the like. In addition, the thickness of skirt 72 influences the outlet pressure produced by the pump, so that lids 70 with different thickness of skirts 72 may be used to provide different outlet pressures. In addition, the inner surface of skirt 72 may be provided with one or more grooves, as shown at 77 in FIG. 8b, to produce a pulsatile output.

Referring now to FIGs. 9a, 9b, 9c, and 10a, 10b, thermal treatment apparatus according to the present invention preferably includes two thermal sensor assemblies 8 and 10 for measuring the temperature of fluid circulating into and out of catheter 2, respectively. Thermal sensor assemblies 8 and 10 are preferably enclosed within a common housing 80 and closed by a common cover 81. Thermal sensor assembly 8 near the inlet end of catheter 2 includes a thermal sensor element 82 received within a rectangular recess formed in a metal thermal coupling member 83. The opposite face of the coupling member is formed with a recess for receiving a metal tube 84 connectible to an inlet tube 85 near the inlet end of the catheter. Thermal sensor assembly 10 similarly includes a thermal sensor element 86 received within a recess formed in another metal thermal coupling member 87. The opposite face of member 87 is similarly formed with a recess for receiving a metal tube 88 adapted to be coupled to an outlet tube 89 near the outlet end of the catheter. Electrical connections are made to the two thermal sensor elements 82 and 86 via a cable 90 leading to controller 12 in FIG. 1. Metal tubes 84 and 88 and inlet and outlet tubes 85 and 89 are preferably disposable.

The two thermal coupling members 83, 87, as well as the two tubes 84, 88, are of a metal, such as stainless steel, having relatively good thermal conductivity. Coupling members 83, 87 include relatively thin web portions 83a, 87a, respectively, between thermal sensor elements 82, 86 and metal tubes 84, 88, so as to provide a good thermal coupling between the fluid flowing through the two metal tubes and their respective thermal sensor elements. Cover 81, fixed to the common housing 80 in any suitable manner, preferably presses metal tubes 84, 88 firmly against their respective metal coupling members 83, 87.



As shown in FIG. 9b, cover 81 may include extensions 81a, and housing 80 may respectively include depressions 80a for receiving extensions 81a of cover 81. Cover 81 is threaded into the chamber defined by depressions 80a of housing 80, pressing each of metal tubes 84 and 88 firmly against their respective metal coupling members 83 and 87.

Another possible configuration is shown in FIGs. 10a and 10b, wherein housing 80 features the shape of "H", and cover 81 presses each of metal tubes 84 and 88 firmly against their respective metal coupling members 83 and 87, and the central segment of housing element 80. Cover 81 may be fixed to the common H-shaped housing 80 in a suitable manner.

As shown in FIG. 1, thermal treatment apparatus according to the present invention may further include an air trapping element for trapping air circulating in the closed system. Air trapping element 7 may be in the form of a hung container 7c, which is preferably flexible and made of plastic, and controllably connectable to the closed system by means of two tubular elements 7d and 7e, and two valve members 7a and 7b. Container 7c, tubular elements 7d and 7e, and valve members 7a and 7b are preferably disposable.

Valve members 7a and 7b may controllably allow or block fluid circulation into and out of container 7c. When fluid is allowed to circulate through container 7c, the air found in the circulating fluid is trapped within the container.

Air trapping element 7 is preferably used for priming the system.

Thermal treatment apparatus according to the present invention preferably includes a disposable set, including: (a) different configurations of catheter 2 for different types of treatments; and (b) a tubing assembly, including: tubular element 3 of temperature-setting device 4; peristaltic tube 66 of pump 6; metal tubes 84 and 88 of thermal sensor assemblies 8 and 10; air trapping element 7; valve members such as 2a, 7a and 7b; and other tubular elements constituting the closed system of circulating fluid.

The overall operation of a thermal treatment apparatus including a temperature-setting device according to the present invention is as follows:

The configuration of catheter 2 is selected according to the specific type of treatment; catheter 2 is then connected to the disposable tubing assembly; tubular element 3 is placed in a suitable embodiment of temperature-setting device 4; peristaltic tube 66 is placed in pump 6; and metal tubes 84 and 88 are placed within thermal sensor assemblies 8 and 10 respectively.

Valve members 7a and 7b are set to allow circulation of fluid through air trapping element 7, and a minimal quantity (about 20-50 ml) of fluid is then introduced into the closed system via valve member 2a. Priming of the system is then carried out by activating pump 6 and circulating the fluid through air trapping element 7, thereby trapping air found in the system.

Valve members 7a and 7b are then set to block cir-

culation of fluid through air trapping element 7, thereby directing the fluid to circulate through the main tube of the system.

An additional quantity of fluid is added at this stage to inflate thermal treating section 22 to its operational volume, if required.

Pump 6 is then switched off, and a quantity of fluid is pumped out of the system via valve member 2a, in order to deflate thermal treating section 22 and to allow the insertion of catheter 2 into the subject's body cavity.

Referring now to FIGs. 4 and 5, catheter 2 is inserted into a subject's body cavity until inflatable anchoring section 21 at the proximal end passes through the neck of the cavity. An unheated fluid, preferably air, is introduced via inlet 27 and passageway 28 into the interior of anchoring section 21 to inflate it. This anchors section 21 in the subject's body cavity, whereupon heating section 22 of the catheter extends through the targeted tissue to be treated.

The quantity of fluid that was pumped out of the system for deflating thermal treating section 22 is now pumped into the system via valve member 2a for inflating thermal treating section 22 while placed within the subject's body cavity.

Referring now to FIGs. 6 and 7, wherein anchoring section 21 is made as an integral part of thermal treating section 22, and thermal treating section 22 features any geometrical shape, while using this configuration, the quantity of fluid that was pumped out of the system for deflating thermal treating section 22 is now pumped into the system via valve member 2a for inflating thermal treating section 22 while placed within the subject's body cavity. If required, an additional quantity of fluid is pumped into the system via valve member 2a so as to fill the particular body cavity, thereby efficiently heating or cooling the tissues therein.

The fluid is then circulated by peristaltic pump 6 through the closed system including thermal treating section 22 of the catheter and tubular element 3 of the temperature-setting device.

During circulation, tubular element 3 which is electrically connected to transformer 11 (FIG. 1), converts electrical energy to heat, thereby heating the fluid circulating therethrough. Alternatively, tubular element 3 may be placed in the embodiment shown in FIGs. 2a and 2b, thereby cooling the fluid circulating therethrough. Thus, temperature-setting device 4 may be used to alternately heat and cool the fluid circulating in the system by alternately placing tubular element 3 within embodiments of the device functioning as heaters and coolers.

Alternatively, tubular element 3 may be placed in the embodiment shown in FIGs. 3a and 3b, thereby alternately heating and cooling the circulating fluid using the same embodiment.

Sensor assemblies 8 and 10, electrically connected to controller 12, sense the temperature of fluid near the inlet and outlet ends of the catheter, respectively. Controller 12 maintain the desired temperature by controlling the duty cycle of transformer 11, and therefore the

heating level of tubular element 3.

Sensor 7, electrically connected to controller 12, senses the temperature of tubular element 3. Controller 12 interrupts the operation of the overall system upon over-heating of tubular element 3.

While using the configurations of catheter 2 shown in FIGs. 4-7, only inflated thermal treating section 22 of the catheter is effective to heat a targeted tissue, because of the thermal insulation provided by the unheated air within insulating chambers 30. While using the configuration shown in FIGs. 4 and 5, the insulation is further provided by anchoring section 21.

Accordingly, the fluid applied to inflatable thermal treating section 22 may be heated to a relatively high temperature for application to the targeted tissues, with less danger of unduly heating untargeted tissues contacted by the catheter. The inflation of thermal treating section 22 also presses that section firmly against the targeted tissue to be thermally treated thereby further enhancing the heating effects.

Drain opening 32 at the proximal end of the catheter, and passageway 33 through the catheter, provide a drain for body fluids or enable the introduction of drugs into the body cavity.

While the invention has been described with respect to a limited number of embodiments, it will be appreciated that many variations, modifications and other applications of the invention may be made.

#### Claims

1. A temperature-setting device for providing a predetermined temperature to a quantity of fluid circulating therethrough, comprising:
  - (a) a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to electrically and thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;
  - (b) a housing element for receiving said tubular element, said housing element including fastening elements, including:
    - (i) a connector member having relatively good electrical conductivity, said connector member connectable to an electrical circuit;
    - (ii) a fastening member for anchoring said tubular element between said fastening member and said connector member; and
  - (c) a transformer element connectable to said electrical circuit.
2. The device of claim 1, wherein said device further includes a sensor for sensing the temperature of said tubular element.
3. The device of claim 1 or 2, wherein said transformer element and said sensor are electrically connected to a controller, and said controller controls the duty cycle of said transformer element according to the temperature sensed by said sensor.
4. The device of claim 1 or 2, wherein said transformer element and said sensor are electrically connected to a controller, and said controller interrupts the operation of said transformer element and said electrical circuit upon a certain value of temperature sensed by said sensor.
5. The device of anyone of claims 1 to 4, wherein said housing element features a recess for receiving said tubular element, and a contact between said tubular element and said sensor is established upon mounting of said tubular element in said recess under pressure.
6. The device of anyone of claims 1 to 5, wherein the voltage produced in said electrical circuit is about 1-5 volts.
7. A cooling device for cooling a quantity of fluid circulating therethrough, comprising:
  - (a) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;
  - (b) a housing element comprising a thermal conducting member disposed within a bath of a cooling substance, said thermal conducting member having a recess for receiving said tubular element, said recess defining a relatively lowered area for trapping cold air, said thermal conducting member featuring extensions for increasing the contact area between said thermal conducting member and said cooling substance.
8. A temperature-setting device for alternately heating and cooling a quantity of fluid circulating therethrough, comprising:
  - (a) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;
  - (b) a heating housing element for receiving said tubular element, said housing element detachably connectable to a heating source;

and

(c) a cooling housing element for receiving said tubular element, said housing element detachably connectable to a cooling source,

said tubular element transferable between said heating housing element and said cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

9. A temperature-setting device for alternately heating and cooling a quantity of fluid circulating there-through, comprising:

(a) a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to electrically and thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;

(b) a heating housing element for receiving said tubular element, said housing element including fastening elements, including:

(i) a connector member having relatively good electrical conductivity, said connector member connectable to an electrical circuit;

(ii) a fastening member for anchoring said tubular element between said fastening member and said connector member;

(c) a transformer element connectable to said electrical circuit; and

(d) a cooling housing element comprising a thermal conducting member disposed within a bath of a cooling substance, said thermal conducting member having a recess for receiving said tubular element, said recess defining a relatively lowered area for trapping cold air, said thermal conducting member featuring extensions for increasing the contact area between said thermal conducting member and said cooling substance,

said tubular element transferable between said heating housing element and said cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

10. Thermal treatment apparatus for selectively treating a targeted tissue adjacent a subject's body cavity, comprising a closed system of circulating fluid and a controller for controlling said closed system, said closed system including:

(a) a temperature-setting device for providing a predetermined temperature to a quantity of fluid circulating therethrough, including:

(i) a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to electrically and thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;

(ii) a housing element for receiving said tubular element, said housing element including fastening elements, said fastening elements including a connector member having relatively good electrical conductivity connectable to an electrical circuit, and a fastening member for anchoring said tubular element between said fastening member and said connector member; and

(iii) a transformer element connectable to said electrical circuit, said transformer element electrically connected to said controller;

(b) a catheter insertable into a body cavity, said catheter connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said catheter including a thermal treating section for thermally treating a targeted tissue adjacent said body cavity by circulating fluid of a predetermined temperature through said thermal treating section, said catheter being disposable;

(c) a pump for pumping said fluid of predetermined temperature through said closed system, said pump connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said pump electrically connected to said controller; and

(d) thermal sensor assembly for sensing the temperature of fluid circulating into said catheter, said thermal sensor assembly having two ends, one of said ends connectable to said catheter and the other of said ends connectable to said tubular element of said temperature-setting device by means of said insulating tubular elements, said thermal sensor assembly electrically connected to said controller.

11. The apparatus of claim 10, wherein said apparatus further includes a second thermal sensor assembly for sensing the temperature of fluid circulating out of said catheter, said second thermal sensor assembly having two ends, one of said ends connectable to said catheter and the other of said ends connect-

able to said pump by means of said insulating tubular elements, said second thermal sensor assembly electrically connected to said controller.

12. The apparatus of claim 10 or 11, wherein said apparatus further includes an air trapping element for trapping air circulating in the system, said air trapping element comprising a hung container connectable to said closed system, said air trapping element being disposable. 5
13. The apparatus of anyone of claims 10 to 12, wherein said temperature-setting device further includes a sensor for sensing the temperature of said tubular element, said sensor electrically connected to said controller. 10
14. The apparatus of claim 13, wherein said controller controls the duty cycle of said transformer element according to the temperature sensed by said sensor. 15
15. The apparatus of claim 13 or 14, wherein said controller interrupts the operation of said transformer element, said electrical circuit and said closed system upon a certain value of temperature sensed by said sensor. 20
16. The apparatus of anyone of claims 13 to 15, wherein said housing element of said temperature-setting device features a recess for receiving said tubular element, and a contact between said tubular element and said sensor is established upon mounting of said tubular element in said recess under pressure. 25
17. The apparatus of anyone of claims 10 to 16, wherein the voltage produced in said electrical circuit of said temperature-setting device is about 1-5 volts. 30
18. The apparatus of anyone of claims 10 to 17, wherein said tubular element of said temperature-setting device, said insulating tubular elements and other tubular elements constituting the closed system are disposable. 35
19. Thermal treatment apparatus for selectively treating a targeted tissue adjacent a subject's body cavity, comprising a closed system of circulating fluid and a controller for controlling said closed system, said closed system including: 40
- (a) a cooling device for cooling a quantity of fluid circulating therethrough, including: 45
- (i) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, said tubular element

having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;

(ii) a housing element including a thermal conducting member disposed within a bath of a cooling substance, said thermal conducting member having a recess for receiving said tubular element, said recess defining a relatively lowered area for trapping cold air, said thermal conducting member featuring extensions for increasing the contact area between said thermal conducting member and said cooling substance;

(b) a catheter insertable into a body cavity, said catheter connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said catheter including a thermal treating section for thermally treating a targeted tissue adjacent to said body cavity by circulating a cooled fluid through said thermal treating section, said catheter being disposable;

(c) a pump for pumping said cooled fluid through said closed system, said pump connectable to said tubular element of said cooling device by means of said insulating tubular element, said pump electrically connected to said controller; and

(d) thermal sensor assembly for sensing the temperature of fluid circulating into said catheter, said thermal sensor assembly having two ends, one of said ends connectable to said catheter and the other of said ends connectable to said tubular element of said cooling device by means of said insulating tubular elements, said thermal sensor assembly electrically connected to said controller.

20. The apparatus of claim 19, wherein said tubular element of said temperature-setting device, said insulating tubular elements and other tubular elements constituting the closed system are disposable. 40
21. Thermal treatment apparatus for selectively treating a targeted tissue adjacent a subject's body cavity by heating said targeted tissue, comprising a closed system of circulating fluid and a controller for controlling said closed system, said closed system including: 45
- (a) a temperature-setting device for providing a predetermined temperature to a quantity of fluid circulating therethrough, including: 50
- (i) a tubular element having relatively good

thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable; and

(ii) a heating housing element for receiving said tubular element, said housing element detachably connectable to a heating source.

(b) a catheter insertable into a body cavity, said catheter connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said catheter including a thermal treating section for thermally treating a targeted tissue adjacent said body cavity by circulating fluid of a predetermined temperature through said thermal treating section, said catheter being disposable;

(c) a pump for pumping said fluid of predetermined temperature through said closed system, said pump connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said pump electrically connected to said controller; and

(d) thermal sensor assembly for sensing the temperature of fluid circulating into said catheter, said thermal sensor assembly having two ends, one of said ends connectable to said catheter and the other of said ends connectable to said tubular element of said temperature-setting device by means of said insulating tubular elements, said thermal sensor assembly electrically connected to said controller.

22. The apparatus of claim 21 for selectively treating a targeted tissue adjacent a subject's body cavity by alternately heating and cooling said targeted tissue, wherein said temperature-setting device further includes a cooling housing element for receiving said tubular element, said housing element detachably connectable to a cooling source, said tubular element transferable between said heating housing element and said cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

23. The apparatus of claim 22, wherein said temperature-setting device comprises:

(a) a tubular element having relatively low electrical conductivity and good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to electrically and thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;

(b) a heating housing element for receiving said tubular element, said housing element including fastening elements, including:

(i) a connector member having relatively good electrical conductivity, said connector member connectable to an electrical circuit;

(ii) a fastening member for anchoring said tubular element between said fastening member and said connector member;

(c) a transformer element connectable to said electrical circuit, said transformer element electrically connected to said controller; and

(d) a cooling housing element comprising a thermal conducting member disposed within a bath of a cooling substance, said thermal conducting member having a recess for receiving said tubular element, said recess defining a relatively lowered area for trapping cold air, said thermal conducting member featuring extensions for increasing the contact area between said thermal conducting member and said cooling substance,

said tubular element transferable between said heating housing element and said cooling housing element, thereby alternately heating and cooling the fluid circulating therethrough.

24. Thermal treatment apparatus for selectively treating a targeted tissue adjacent a subject's body cavity by heating and cooling said targeted tissue, comprising a closed system of circulating fluid and a controller for controlling said closed system, said closed system including:

(a) a temperature-setting device for heating and cooling a quantity of fluid circulating therethrough, including:

(i) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;

(ii) a housing element for alternately heating and cooling said tubular element, said housing element including two thermal conducting plates, each having a recess, said recesses defining a tunnel for receiving said tubular element under pressure;

(iii) a heating source detachably connectable to said housing element; and

(iv) a cooling source detachably connectable to said housing element, said housing

element controllably heating and cooling said tubular element, thereby alternately heating and cooling the fluid circulating therethrough;

- (b) a catheter insertable into a body cavity, said catheter connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said catheter including a thermal treating section for thermally treating a targeted tissue adjacent said body cavity by circulating fluid of a predetermined temperature through said thermal treating section, said catheter being disposable;
- (c) a pump for pumping said fluid of predetermined temperature through said closed system, said pump connectable to said tubular element of said temperature-setting device by means of said insulating tubular element, said pump electrically connected to said controller; and
- (d) thermal sensor assembly for sensing the temperature of fluid circulating into said catheter, said thermal sensor assembly having two ends, one of said ends connectable to said catheter and the other of said ends connectable to said tubular element of said temperature-setting device by means of said insulating tubular elements, said thermal sensor assembly electrically connected to said controller.
25. The apparatus of claim 24, wherein said temperature-setting device comprises:
- (a) a tubular element having relatively good thermal conductivity for receiving a quantity of circulating fluid, said tubular element having two ends connectable to thermally insulating tubular elements, said tubular element and said insulating tubular elements being disposable;
- (b) a housing element for alternately heating and cooling said tubular element, said housing element comprising two thermal conducting plates, each having a recess, said recesses defining a tunnel for receiving said tubular element under pressure; and
- (c) peltier heat pump elements detachably connectable to said thermal conducting plates,
- said peltier heat pump elements alternately heating and cooling said thermal conducting plates, thereby alternately heating and cooling the fluid circulating through said tubular element.
26. The apparatus of anyone of claims 10 to 18,

wherein said catheter includes a proximal end formed with an inflatable thermal treating section to be located within the body cavity, and a distal end to be located externally of the body cavity; said catheter being formed with first and second passageways extending from said distal end to said inflatable thermal treating section for circulating fluid of a predetermined temperature through said inflatable thermal treating section.

27. The apparatus of claim 26, wherein said catheter further includes thermal insulation surrounding said first and second passageways from close to said distal end to close to said inflatable thermal treating section, said thermal insulation including a plurality of separate compartments containing a non-heated fluid, said compartments extending axially along the catheter, thereby the inflatable thermal treating section and the targeted tissue in its proximity may be heated to a desired temperature without correspondingly heating non-targeted tissues.
28. The apparatus of anyone of claims 10 to 18, 26, 27, wherein said catheter includes a proximal end formed with an inflatable anchoring section for anchoring the catheter in the body cavity, a distal end to be located externally of the body cavity, and an inflatable thermal treating section adjacent said proximal end to be located near the targeted tissue; said catheter being formed with first and second passageways extending from said distal end to said inflatable thermal treating section for circulating fluid of a predetermined temperature through said inflatable thermal treating section, and a third passageway extending from said distal end to said inflatable anchoring section for introducing unheated fluid into said inflatable anchoring section.
29. The apparatus of claim 19 or 20, wherein said catheter includes a proximal end formed with an inflatable thermal treating section to be located within the body cavity, and a distal end to be located externally of the body cavity; said catheter being formed with first and second passageways extending from said distal end to said inflatable thermal treating section for circulating cooled fluid through said inflatable thermal treating section.
30. The apparatus of claim 29, wherein said catheter further includes thermal insulation surrounding said first and second passageways from close to said distal end to close to said inflatable thermal treating section, said thermal insulation including a plurality of separate compartments containing a non-cooled fluid, said compartments extending axially along the catheter, thereby the inflatable thermal treating section and the targeted tissue in its proximity may be cooled to a desired temperature without correspondingly cooling non-targeted tissues.
31. The apparatus of anyone of claims 19, 20, 29, 30, wherein said catheter includes a proximal end

formed with an inflatable anchoring section for anchoring the catheter in the body cavity, a distal end to be located externally of the body cavity, and an inflatable thermal treating section adjacent said proximal end to be located near the targeted tissue; said catheter being formed with first and second passageways extending from said distal end to said inflatable thermal treating section for circulating cooled fluid through said inflatable thermal treating section, and a third passageway extending from said distal end to said inflatable anchoring section for introducing uncooled fluid into said inflatable anchoring section.

32. The apparatus of anyone of claims 19, 20, 29, 30, 31, wherein said apparatus further includes an air trapping element for trapping air circulating in the system, said air trapping element comprising a hung container controllably connectable to said closed system, said air trapping element being disposable.

33. The apparatus of anyone of claims 10 to 18, 26, 27, 28, wherein said pump includes:

(a) a housing formed with a substantially cylindrical cavity having an inner surface, said housing provided with a lid, said lid having a depending skirt removably engageable within said cylindrical cavity so as to form an inset lining around a part of said inner surface;  
(b) a rotor rotatably mounted within said cylindrical cavity, said rotor carrying rollers; and  
(c) a peristaltic tube, said peristaltic tube being disposable, such that, when said depending skirt is not engaged in said cylindrical cavity, the peristaltic tube may be easily inserted between said rollers and said inner surface and, when said depending skirt is engaged in said cylindrical cavity, the peristaltic tube is engaged between said rollers and said inset lining such that rotation of said rotor pumps fluid through the peristaltic tube.

34. The apparatus of anyone of claims 19, 20, 29 - 32, wherein said pump includes:

(a) a housing formed with a substantially cylindrical cavity having an inner surface, said housing provided with a lid, said lid having a depending skirt removably engageable within said cylindrical cavity so as to form an inset lining around a part of said inner surface;  
(b) a rotor rotatably mounted within said cylindrical cavity, said rotor carrying rollers; and  
(c) a peristaltic tube, said peristaltic tube being disposable, such that, when said depending skirt is not engaged in said cylindrical cavity, the peristaltic tube may be easily inserted

between said rollers and said inner surface and, when said depending skirt is engaged in said cylindrical cavity, the peristaltic tube is engaged between said rollers and said inset lining such that rotation of said rotor pumps fluid through the peristaltic tube.

35. The apparatus of anyone of claims 10 to 18, 26, 27, 28, 33, wherein said thermal sensor assembly includes: a thermal sensor; a disposable metal tube connectable to the end of a passageway of the catheter to receive the fluid flowing therethrough; a metal thermal coupling member formed with a recess on one face for receiving the thermal sensor therein, a recess on the opposite face complementary to the shape of the metal tube for receiving the metal tube therein, and a relatively thin web between the two recesses; and a cover pressing said metal tube to said thermal coupling member.

36. The apparatus of anyone of claims 19, 20, 29 to 32, 34, wherein said thermal sensor assembly includes: a thermal sensor; a disposable metal tube connectable to the end of a passageway of the catheter to receive the fluid flowing therethrough; a metal thermal coupling member formed with a recess on one face for receiving the thermal sensor therein, a recess on the opposite face complementary to the shape of the metal tube for receiving the metal tube therein, and a relatively thin web between the two recesses; and a cover pressing said metal tube to said thermal coupling member.




FIG. 1



FIG 2a





FIG 2b

FIG. 3a






FIG. 3b



**FIG. 42**




FIG. 41




FIG. 5a




FIG. 5B






FIG. 5C






FIG. 8c




FIG. 9c





FIG. 9a




FIG. 9b




FIG. 10a




FIG. 10b

特開平10-33582

(43) 公開日 平成10年(1998) 2月10日

(51) Int.Cl. <sup>6</sup>	識別記号	片内整理番号	F I	技術表示箇所
A 6 1 F 7/12			A 6 1 F 7/12	Z
7/00	3 0 0		7/00	3 0 0
A 6 1 M 25/00	4 0 5		A 6 1 M 25/00	4 0 5 D

審査請求 未請求 請求項の数56 O L (全 18 頁)

(21) 出願番号	特願平9-98992	(71) 出願人	595049529 アルゴームド リミッティッド イスラエル国、ヘルツリア 46766、メデ イナート ハイヒューデウム ストリート 60
(22) 出願日	平成9年(1997) 4月18日	(72) 発明者	ウジ エシエル イスラエル国、ヘルツリア、アチ ダカール 28
(31) 優先権主張番号	0 8 / 6 3 2 8 3 0	(72) 発明者	ジェイ グラハム クラブツリー イスラエル国、ヘルツリア、ハナディブ 35
(32) 優先日	1996年4月18日	(74) 代理人	弁理士 大西 正信
(33) 優先権主張国	米国 (U S)		

最終頁に続く

(54) 【発明の名称】 温度設定装置およびこの装置を用いた温度治療装置および方法

(57) 【要約】

【課題】 最小限の循環流体を用いるだけで、流体加熱のエネルギー消費が最小であり、流体が漏れた場合に生じるダメージを最小に抑えることができるような流体誘起温度治療により、目標組織を選択的に治療する。

【解決手段】 温度治療装置は、循環流体を受ける比較的低導電性が低いチューブ状エレメント 3 と、このチューブ状エレメントを受容して固定保持するとともに、チューブ状エレメントを電気回路と電気接続させるためのハウジングエレメントと、この電気回路に電気接続可能なトランス 11 とから構成される。チューブ状エレメントはその両端が、電気絶縁されるとともに断熱された絶縁チューブ（配管）エレメントに接続される。チューブ状エレメント 3 の温度を検出するセンサ 9 を有し、センサ 9 およびトランス 11 はコントローラ 12 と電気接続される。センサ 9 により検出された温度に基づいてトランス 11 のデューティサイクルを制御する。

